



Subwoofer Amp & Stereo Amp output



- Class AB power amplifier design.
- Include auto standby power saving mode.
- Phase switch (0°/ 180°).
- Speaker configuration can be any match
- Short circuit/Temperature/DC Fault protection.
- Limiter circuit reduces distortion and increases intelligibility for guaranteed powerful and clear sound.

BT105N

Specifications

Item	
Power Output(RMS)	Subwoofer - 70W/ 4Ω
	Stereo - 30W*2/ 8Ω
Amplifier Type	Class AB
Frequency Response(AMP.)	20Hz~20KHz (0dB ~ -3dB)
Low Pass Frequency	20Hz~150Hz
Input Sensitivity	100mV
T.H.D	≤ 0.1 % @ Full Power
Noise	≤ 4mV
S/N	≥ 70dB
Auto Standby	YES
Standby Power	≤ 1W
Phase Switch	0°/ 180°
Crossover	30Hz~120Hz(Frequency adjustable)
Audio Input	Line In RCA Jack
Audio Output	Speaker Out Banana Jack
Dimensions(WxHxD)	274x284x110mm
Net Weight	6kg
Power Supply	220-240 Vac, 110-120 Vac For Certain Markets

5.8GHz



Can be installed 5.8G receiver box and TX-mixer with the use

BanTech®

Dedication to design & development on new products

CHIA BAN

BANTECH-TAIWAN
TEL:+886-7-787-5611

E-mail: bantech@chiaban.com.tw

