



Multitude subwoofer amplifier 3 unit 150W powered amplifier

- Include 3-150W Subwoofer Amp.
- Low power consumption.
- Low distortion amplifier.
- Include standby power saving mode.
- Signal compression circuit.
- Use high efficiency power mosfet.
- Amp efficiency $\geq 90\%$.
- Short circuit/Temperature/Overvoltage protection.



BTD3150

Specifications	
Model	BTD3150
Power Output(RMS)	150W//4 Ω *3
T.H.D	$\leq 0.1\%$ @ 10W/4 Ω
	$\leq 1\%$ @ 150W/4 Ω
Amplifier Type	Class D
Frequency Response	20Hz~150Hz
Input Sensitivity	110mV
Noise	<0.5mV
S/N	≥ 90 dB
Auto Standby	YES
Standby Power	≤ 1 W
Phase Switch	0°/ 180°
Crossover	30Hz~120Hz(Frequency adjustable)
Audio Inputs	1.High Level Speakon Connector 2.Low Level single RCA Jack 3.LFE RCA Jack
Audio Output	Output Speakon Connector
Dimensions(WxHxD)	484x380x105mm
Net Weight	6kg
Power Supply	120-240 Vac For Certain Markets

BanTech® Dedication to design & development on new products

CHIA BAN

BANTECH-TAIWAN
TEL:+886-7-787-5611
E-mail: bantech@chiaban.com.tw